

allegro²™

Descending from a long line of trusted rugged handhelds, outstanding quality and unsurpassed ruggedness are in the Allegro 2's genes. Designed for the data-intensive, every aspect of the Allegro 2 was carefully engineered to provide the ultimate in productivity and efficiency. The following specifications are just the tip of the iceberg.

PROCESSOR

- 1.0 GHz ARM Cortex A8 i.MX53 processor

OPERATING SYSTEM AND SOFTWARE

- Microsoft® Windows Embedded Handheld 6.5.3
- Microsoft Office Mobile 2010* (Word Mobile, Excel Mobile, PowerPoint Mobile, SharePoint Workspace Mobile, OneNote Mobile, Contacts, Calendar & Email)
- Multiple languages (English, French, Spanish, German, Portuguese)
- Adobe Reader® LE

MEMORY AND DATA STORAGE

- 512 MB RAM
- 8 GB flash storage
- User-accessible micro SD/SDHC slot

DISPLAY

- Active viewing area: 4.2 inch (107 mm) VGA LCD TFT (640 x 480) Landscape Display
- High-visibility backlit LCD



TOUCHSCREEN

- Projected capacitive touch interface
- Chemically-strengthened glass
- Scratch-resistant screen

KEYBOARD

- Full numeric and QWERTY keypad with user-assignable keys
- Adjustable backlit keys
- JS Power Keys Shortcuts
- OEM configurable/customizable

PORTS

- COM1, RS-232C 9-pin D connector with 5VDC power output on pin 9 software-enabled
- USB host (Full A), USB client (Micro B)
- 12, 24VDC input, 10-36V unregulated
- 3.5 mm audio jack, supports speaker/microphone or stereo output (pin detect)
- I/O module OEM configurable/customizable
- IO docking ports for charging, USB port connector protector



BATTERY

- Intelligent Li-Ion battery 3.7VDC @ 10600 mAh, 38.7 Whr
- Operates 20 hours or more on one charge
- Charges in 2 to 4 hours
- Battery easily changeable in field
- Optimized for excellent performance in cold temperatures

PHYSICAL

- Size, Standard models: 5.4" w x 10.2" l x 1.6" d (138 mm x 256 mm x 40 mm)
- Weight: 2 lbs (908 g), with battery
- Durable hardened plastic in a shear-proof and shock-resistant design
- Strong chemical resistance
- Comfortable, wide hand strap
- Easy-to-grip, impact-absorbing bumpers
- OEM customizable expansion area

JUNIPER RUGGED™

- IP68 waterproof and dustproof
- Operating temperature: -22F to 140F (-30C to 60C)
- Storage temperature: -22F to 158F (-30C to 70C)
Note: Bluetooth® wireless technology is rated to -4 F (-20 C)
- Shockproof: multiple drops from 4' (1.22 m) onto concrete
- MIL-STD-810G test procedures: Method 500.5 Low Pressure (Altitude); Method 501.5 High Temperature; Method 502.5 Low Temperature; Method 503.5 Temperature Shock; Method 506.5 Rain; Method 507.5 Humidity; Method 510.5 Sand and Dust; Method 512.5 Immersion; Method 514.6 Vibration; Method 516.6 Shock

WIRELESS CONNECTIVITY OPTIONS

- Bluetooth® wireless technology, 2.1 +EDR, Class 1.5, range greater than 100 feet (30 m)
- Wi-Fi® 802.11b/g/n with extended range
- 3.75G modem - Pentaband Worldwide (Geo 3G model only)
- Frequencies: HSPA+/UMTS: 800/850/900/1800/1900/2100MHz
- Data communication interface



CAMERA (GEO MODELS)

- 5 MP resolution with autofocus and LED illuminator + video capture
- Juniper Geotagging™: embed and emboss photo with date, time, and GPS position

GPS/GNSS (GEO MODELS)

- High-sensitivity GPS/GLONASS/SBAS receiver
- User settings for enhanced performance under canopy
- Accuracy: SBAS 2 meters; autonomous 5 meters

- NMEA-0183 ver. 4.0 out
- 72-channel u-blox M8 engine
- JNav GNSS positioning and navigation app

CERTIFICATIONS AND STANDARDS

- FCC Class B
- CE Marking (applicable EMC, R&TTE, and LVD directives)
- Industry Canada
- EN60950 Safety

STANDARD ACCESSORIES

- 10600 mAh battery
- AC wall charger with international plug kit
- Micro USB client sync cable
- Quick Start Guide
- Adjustable hand strap
- Shipping box
- Screwdriver
- Stylus with tether
- 2-year warranty

OPTIONAL ACCESSORIES

- A2 Single Ethernet Dock: provides power/charging, USB client sync, and 10/100 Base-T Ethernet interface
- 12VDC Vehicle Charging Cable
- Replacement Stylus Kit
- Holster Case

Single and Multi-year extended service plans are available.

© Copyright 4/17 Juniper Systems, Inc. Specifications are subject to change without notice. All trademarks are registered or recognized by its respective owners. Windows Mobile and the Windows logo are trademarks of the Microsoft group of companies.

*Not included on OEM programs

